



Second skin feeling. Extreme light, flexibility, dexterity and comfort. 18 gauge, micro-foam nitrile.

KEY FEATURES

- Second skin feeling. Extremely light glove with perfect dexterity, flexibility and minimum hand fatigue
- Around 40% lighter than a standard 13 gauge nitrile glove
- Super soft, comfortable and perfect fit
- 10-finger touchscreen functionality enables you to use all touch screen devices on the job
- OEKO-TEX standard 100 certified for skin friendly
- Individual pack available for retail shops




PRODUCT DETAILS

Liner	Nylon
Gauge	18
Coating	Nitrile
Finishing	Micro-foam
Colour	Blue / Blue
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose, precision works in dry or light oily conditions.

Such as fine assembly and disassembly, equipment maintenance, inspection, sorting, handling small parts, general handling, adjusting systems...



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	4
Blade cut - coupe test (Index) (min.0 to max. 5):	1
Tear (min.0 to max. 4):	1
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



4111X

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-002 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

