



Super cold resistance & level C/5 cut protection. Extra flexibility, softness and comfort. 10 gauge, sandy latex.

KEY FEATURES

- Super cold resistance
- Cut level 5 and TDM cut level C protection
- 10 gauge brushed acrylic cut resistant liner guarantees excellent cold resistance and provides extra comfort & softness compared with the standard 7 gauge one in the market
- Sandy latex coating provides excellent grip in both dry and wet working condition
- Super softness, flexibility and comfort
- Good fitting




PRODUCT DETAILS

Liner	Cut resistant yarn, thermo yarn, mixed with others
Gauge	10
Coating	Latex
Finishing	Sandy
Colour	Blue / Black
Size	8,9,10,11
Packing	12 pairs/pack, 120 pairs/carton
Tariff number	61161020


RECOMMENDED APPLICATIONS

Works in contact cold conditions with or without cut hazards in dry or a little wet condition, or for contact heat protection in dry condition.

Such as outdoor works, cold storage, maintenance, handling sharp or rough edge parts, machine operation, logistics, warehouse works and etc.



CERTIFICATION

 EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **2**
Blade cut - coupe test (Index) (min.0 to max. 5): **5**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **2**
Cut resistance from sharp objects EN ISO
13997:1999 (min. A to max. F, X - not tested): **C**
Impact protection (P if pass, F if failed): **-**

EN388:2016



2542C

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

**EN511:2006 Cold protection:
levels obtained in laboratory tests**

A - Convective cold: min.0 to max. 4
B - Contact cold: min.0 to max. 4
C - Water penetration: (1 if pass, 0 if failed)

EN511:2006



X1X

X = not tested or testing method is unsuitable for the design of the gloves.

**EN407:2004 Heat protection:
levels obtained in laboratory tests**

A - Burning behaviour: X of 4
B - Contact heat: 2 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small drops of molten metal: X of 4
F - Large quantity of molten metal: X of 4

EN407:2004



X2XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 51-818 can normally be 3 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.

Please ensure the products are strictly used within their protection levels.

