



Anti-vibration glove with cut level B protection. Good fitting and comfortable. 10 gauge, latex.

KEY FEATURES

- Good vibration protection glove.
EN ISO 10819: TRm = 0.865, TRh = 0.598
- Cut protection level B (it is tested for the palm area)
- Good fitting and comfortable



PRODUCT DETAILS

| | |
|---------------|---------------------------------|
| Liner | Polyester mixed with other yarn |
| Gauge | 10 |
| Coating | Latex |
| Finishing | |
| Colour | black / black |
| Size | 8,9,10,11 |
| Packing | 6 pairs/pack, 72 pairs/carton |
| Tariff number | 61161020 |

RECOMMENDED APPLICATIONS

Works with vibration hazard or low cut hazard in dry or little wet conditions.

Such as tools with vibration, work with chainsaw, road drills, submersible vibrating machines, grinders.



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

| | |
|--|----------|
| Abrasion (min.0 to max. 4): | 4 |
| Blade cut - coupe test (Index) (min.0 to max. 5): | 1 |
| Tear (min.0 to max. 4): | 4 |
| Puncture (min.0 to max. 4): | 2 |
| Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested): | B |
| Impact protection (P if pass, F if failed): | - |

EN388:2016



4142B

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-500 can normally be 3 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

