

Premium quality cut protection level C glove with extra leather palm, 15 gauge, nitrile

KEY FEATURES

- Premium cut protection level C glove with great flexibility and comfort
- Extra leather in the palm offers a much better puncture protection, more durable and a higher contact heat protection
- Reinforcement in the crotch offers extra durability and more protection while working
- · Very flexible and a lighter weight of the glove liner contributes to more comfort and much less hand fatigue
- Good fitting























PRODUCT DETAILS

Liner

UHMWPE mixed with other yarns

Gauge

15

Coating

Nitrile

Finishing

Foam

Colour

Dark Blue / Grey

Size

8,9,10,11

Packing

6 pairs/pack, 72 pairs/carton

Tariff number

61161020

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or puncture hazard or contact heat hazard in dry or light wet/oily conditions conditions.

Such as handling sharp or rough parts, metal & sheet metal works, stampling press works and etc.





















Xcellent_® 12-900LP

CERTIFICATION



EN21420:2020+A1:2018

Category II

EN388:2016 Mechanical protection:
levels obtained in laboratory tests

Abrasion (min.0 to max. 4):

Blade cut - coupe test (Index) (min.0 to max. 5):

Tear (min.0 to max. 4):

Puncture (min.0 to max. 4):

Cut resistance from sharp objects EN ISO

13997:1999 (min. A to max. F, X - not tested):

Impact protection (P if pass, F if failed):

EN21420:2020+A1:2018 Dexterity (min.0 to max.5): **level 5.**

EN407:2020 Heat protection:

E - Small splashes of molten metal: X of 4 F - Large quantities of molten metal: X of 4

X = not tested or testing method is unsuitable for the design of the gloves.



STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-900LP can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.



