



TDM cut level D, food contact approved, washable up to 36 times. Cost effective. 10 gauge.

## KEY FEATURES

- Food contact approved, TDM cut level D protection.
- Washable up to 36 times, very durable and cost efficient.
- Great dexterity, flexibility & fitting, comfortable.
- Blue colour for easier recognition.
- Ambidextrous design.
- OEKO-TEX standard 100 certified.



## PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	10
Coating	N.A.
Finishing	N.A.
Colour	Blue
Size	6,7,8,9,10,11,12
Packing	1 Pair/pack, 12 pairs/polybag, 120 pairs/carton
Tariff number	61169300

## RECOMMENDED APPLICATIONS

Meat Processing, fish processing, vegetable and fruit processing and etc.



## CERTIFICATION


**CE** EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection: levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **3**  
 Blade cut - coupe test (Index) (min.0 to max. 5): **X**  
 Tear (min.0 to max. 4): **4**  
 Puncture (min.0 to max. 4): **X**  
 Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested): **D**  
 Impact protection (P if pass, F if failed): **-**

EN388:2016



3X4XD

EN420:2003+A1:2009 Dexterity (min.0 to max.5): **level 5.**

**Food Contact Approval Tests, EN1186 results obtained in laboratory tests**

Simulant(s) Used	Test Condition	Result(s) [mg/dm <sup>2</sup> ]	Maximum Permissible Limit [mg/dm <sup>2</sup> ]
3% Acetic Acid	70°C for 2 hours	2.25	10
95% Ethanol	60°C for 2 hours	1.05	10
Iso-octane	40°C for 0.5 hour	<0.500	10

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-260 can normally be 5 years.

## CLEANING

60 °C water wash in 30 minutes. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals, moving machines or electrical risk. Please ensure the products are strictly used within their protection levels.

