



**New Design – thinner 18 gauge cut level D, close to 21 gauge, second skin feeling, micro-foam nitrile.**

## KEY FEATURES

- New design cut level D / A4 glove which is much lighter than normal 18 gauge ones and close to 21 gauge, second skin feeling.
- Perfect dexterity, fitting and flexibility makes it ideal for both general works and precision works.
- Premium quality technical yarns contribute to great comfort, softness, and a smooth feeling.
- Thanks to high quality micro-foam nitrile coating, it offers great grip performance, oil resistance and durability
- The reinforcement in the crotch greatly extends glove life to save your cost and provides extra protection in the weakest area.
- Touch screen functionality.




## PRODUCT DETAILS

Liner	UHMWPE, steel fiber and others
Gauge	18
Coating	Nitrile
Finishing	Micro-foam
Colour	Blue / Black
Size	7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161020

## RECOMMENDED APPLICATIONS

**General purpose or precision works with high cut hazard in dry or light oily conditions.**

Such as precision works, assembly, handling parts with sharp or rough edges, maintenance, general handling, inspection, packaging, sorting...



## CERTIFICATION

**CE** EN ISO 21420:2020

Category II

**EN388:2016 Mechanical protection:  
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	<b>4</b>
Blade cut - coupe test (Index) (min.0 to max. 5):	<b>X</b>
Tear (min.0 to max. 4):	<b>4</b>
Puncture (min.0 to max. 4):	<b>2</b>
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to max. F, X - not tested):	<b>D</b>
Impact protection (P if pass, F if failed):	-

EN388:2016



4X42D

**EN407:2020 Heat protection:  
levels obtained in laboratory tests**

A - Limited flame spread:	X of 4
B - Contact heat:	1 of 4
C - Convective heat:	X of 4
D - Radiant heat:	X of 4
E - Small drops of molten metal:	X of 4
F - Large quantity of molten metal:	X of 4

EN407:2020



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

## STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-981 can normally be 5 years.

## CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

## WARNING

Don't use in case of chemicals or electrical risk.  
Please ensure the products are strictly used within their protection levels.  
Never wear gloves when operating machinery with accessible rotating or other moving parts.

